

NOTICE INVITING TENDER

The Tata Power Company Limited Invites Tenders (Two-Part Bidding Process), from interested and eligible Vendors for the following Works required for its various Transmission Receiving Stations.

A. Summary of the tendered packages:

| Sr. No. | Description | Tender Reference no. | Bid Guarant eeFee / EMD (Rs.) | Tender Fee (Rs.) |
|----------------|-----------------------------------------------------------------------------------------|-----------------------------|--------------------------------------|-------------------------|
| 1. | Reinstatement work post cable laying at Tata Power Parel & Mahalaxmi Receiving Station. | CC26SVP027 | 30,000 /- | 2,000 /- |

Interested bidder is strongly advised not to wait by above time and purchase the tender immediately to get the link for bid submission. This will enable them to communicate/raise queries against the subject tender in time.

For additional technical details and Pre-qualification criteria for the subject works please refer section C below.

B. Guidelines for Participating:

Interested and eligible vendors can participate by submitting the following up to 1500 hours on **Wednesday - 29th October 2025**.

1. Payment of non-refundable Tender Fee, as indicated in table above to be paid by direct deposit in following bank account

Beneficiary Name – The Tata Power Co. Ltd.

Bank Name – HDFC Bank Ltd.

Branch Name – Fort Branch, Mumbai

Address – Maneckji Wadia Building, Nanik Motwani Marg, Fort, Mumbai 400023.

Branch Code – 60

Bank & Branch Code – 400240015

Account No – 00600110000763

Account type – CC

IFSC Code – HDFC0000060

2. Submission of duly signed and stamped Authorization Letter indicating name of authorized person, contact number and e-mail id (mandatory) on Vendor's letterhead. The letter shall also mandatorily include payment details of Tender fee and Tender Reference no **CC26SVP027**.

Authorization Letter along with proof of submission of tender fee should be e-mail to **Ms. Sujata Vishnu Patil** (sujatavishnu.patil@tatapower.com) and copy to **Ms. Vaishali Kachare** (vaishali.Kachare@tatapower.com)

Note: - Once the above-mentioned documents are received, detailed RFP shall be issued through our e-tender system.

3. It is clarified that Bid Guarantee/EMD as mentioned in section “A” above, is not required to be submitted at this stage, and it will be required to be submitted in the form of Bank guarantee at the time of Bid Submission.

C. Addition technical details:

A2. Prequalification Criteria (Technical & Commercial:

| Sr No | Parameter | Tata Power Requirement | Documents to be submitted by vendor to ascertain meeting of Pre-Qualification Requirement |
|-------|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 2 | 3 | 4 |
| (A) | Experience | <p>A) Bidder should have minimum 03 years' experience in RI work (Asphalt), bidder to submit related document for same.</p> <p>B) Bidder must have experience of successfully completing a minimum of following civil works during the past 3 years as on the date of bid opening.</p> <ul style="list-style-type: none"> • Asphalt concrete and Bitumen Macadam (minimum 500 sqm) • Laying of Paver block (Minimum 500 sqm) <p>In case the bidder has a previous association with any of Tata Power Group companies for similar products and services, the performance feedback of the bidder by the Tata Power Group companies shall only be considered for evaluation purpose, irrespective of performance certificates issued by any third organization</p> | <p>Bidder to submit credentials for supporting the noted criteria. Owner has the right to reject the bid in case it is observed that the Bidder does not meet the relevant experience for the subject works</p> |
| (B) | ISO Certifications | <p>Vendor should possess ISO-9001, ISO-14001 and OHSAS-18001 / ISO- 45001 Certification or they should provide an undertaking that they will obtain these certifications for their organization if the work is awarded to them.</p> | <p>Bidder to submit credentials for supporting the noted criteria. Owner has the right to reject the bid in case it is observed that the Bidder does not meet the relevant experience for the subject works.</p> |

| | | | |
|-----|------------------------------|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (C) | Commercial Capability | Average annual turnover of the Vendor for last two financial years shall not be less than INR 30 Lakhs. | Profit and Loss Statements, Balance Sheet, Cash Flow Statements for the Three (3) preceding financial years duly audited and approved by Authorized Audit Firm / CA. |
|-----|------------------------------|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Note -

- 1) Tata Power reserves the right to review and approve / reject the Bidder based on Document Submission.
- 2) The Prequalification Criteria published along with the tender "In Section C.1 Pre-Qualification Criteria" is the total & complete pre-qualification requirement for the tender and shall prevail over any other/additional pre-qualification requirement mentioned elsewhere in the tender.
- 3) Apart from the above PQR bidder must also qualify in Safety evaluation. Details will be shared along with tender documents.

Note: Above Pre-qualification details need not be submitted at this stage. These shall be required to be submitted along with bid submission. At this stage, Interested Vendors who fulfill above criteria need to participate in tender by paying tender fee and submitting authorization letter as detailed in section "B" above.

D. Estimated Quantity: (BOQ)

| Price Bid Format_CC26SVP027_Reinstatement work post cable laying at Tata Power Parel & Mahalaxmi Receiving Staion | | | | |
|------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------|
| Sr. no | Description | Description | Quantity | Unit |
| A. RI work at Mahalaxmi RS | | | | |
| 1 | CISE,EXCAVATION FROM 0 TO 0.5 M | CISE, Excavation for foundation, trenches, pits, paver blocks, etc. (0 to 0.5 m) Excavation for foundations, trenches pits etc. in ordinary soil mixed with boulders of max. dia. 600mm, including removal of vegetation, shoring, strutting, dewatering wherever necessary etc. complete. including shifting and stacking excavated material within an initial lead of 100 m, and then removal and disposing off excavated earth in MCGM / MBMC approved dumping areas (Measurements shall be based on plan dimensions of PCC. No additional payment will be made for slopes, working area, shoring, etc.) Rate shall be inclusive of obtaining necessary permissions from concerned statutory authorities such as Collector, MCGM debris management cell, or permissions stipulated by MBMC etc. for disposing of excavated earth for which available documents shall be provided by Tata Power | 150 | M3 |
| 2 | CISE, LAYING PCC M15 | CISE,CISE,Providing all materials and laying plain cement concrete as leveling course, saddle concrete or complete encasing wherever required including formwork curing etc. Layng PCC M-15 | 5 | M3 |
| 3 | CISE,PROV & LAY CRUSHED STONE SUB BASE C | CISE,GSB:Providing & laying, spreading & compacting specified crushed stone ingranular subbase course including premixing the material in mechanical mixer (pug) will carriage of mixed material laying in uniform layer of 100mm(compactd thickness each) with motor grader onprepared murum surface & compacting with 10 tonne vibratory roller toachieve desired density including all material, labour, machinery, lighing barricating to all lifts & lead maintenance of diversion etc.complete (metal gradation from 90mm to 75mm micron as per MCGM RoadSpecifications clause no.210). | 80 | M3 |
| 4 | CISE,SCRAPING BITUMINOUS SURFACE | CISE,Scraping: Scraping Up to 60mm to 100 mm depth single pass bituminous road surface by using milling machine/JCB etc. including disposal of scraping milled materials in MCGM approved dumping yard or as directed etc. complete. Note: For further passes of 60mm or part there of same rate will be applicable. | 100 | M2 |

| | | | | |
|----------------------------|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|
| 5 | CISE,PROV & LAYING BITUMINOUS MACADAM | CISE,Providing and laying 75mm Bituminous Macadam: Bituminous Macadam: Providing and laying of 75 mm thick compacted full grout using 57mm/50mm size hand broken metal on the prepared surface to a loose thickness of 200mm by rolling with 10 ten roller including spreading , consolidation so as to obtain a compacted thickness of 75mm and spreading hot bitumen 60/70 penetration of approved brand heated to a temperature of 204degree C (400deg. F)by means of pressure distributor at the rate of lbs/100sft covering such area with 12.5mmsize clean size stone metal at the rate of 2.1CM/100sqm and rolling the same with a 10 to 12 tone roller as directed by Tata Power engineer including providing all materials, tools equipment etc. | 350 | M2 |
| 6 | CISE,PROV & LAYIN ASPHALT CONCRETE | CISE, Providing and laying asphalt concrete (075kg/m2): Asphalt Concrete: Providing and laying with paver asphalt concrete comprising of a thin application of fine aggregate premixed with bituminous binder including cleaning wherever required and applying tack coat (bitumen 0.75KG/m2) Bitumen content 6.5% of mix and covered with stone dust so as to obtain the smooth finish including material tools etc.40mm thick Asphalt concrete laying by paver finisher and compaction by 10 to 12 Tone roller | 350 | M2 |
| 7 | CISE,PROV & LAYING WET MIX MACADAM | CISE, Providing and laying compacted Wet Mix Maccadam course as per mix design (MORTH) and consisting of hard quality metal 30% of size 40mm, metal 25% of size 20mm, metal 10% of size 10mm, and 35% of 6mm down and Crusher sand, by cleaning and scarifying existing uneven road surface, including Plant & Machinery for mixing in Pug Mill, laying in uniform layer of 75mm (compactedthickness each) Compaction of the prepare surface with Vibrating roller, Spreading with Paver and rolling with power roller (10 TON)and binded together with lines, grades and cross-section as shown in the attached sketch or as directed by Tata Power Site Engineer for bindage materials, grit, stone dust must be used including providing all materials, tools equipment & barricading etc. | 70 | M3 |
| 8 | P/L 12 mm thick premix seal coat | CISE, Providing &Laying with paver 12 mm thick premix seal coat comprising of a thin application of fine aggregate premix with bituminous binder. Percentage of straight bitumen shall be in the range of 6 to 8% of mix & covered with stone dust so as to obtain a smooth uniform finish including materials, tools, equipment's etc. (Rate includes laying tack coat.) | 350 | M2 |
| B. RI work at Parel | | | | |

| | | | | |
|---|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|
| 1 | CISE, EXCAVATION FROM 0 TO 0.5 M | <p>CISE, Excavation for foundation, trenches, pits, paver blocks, etc. (0 to 0.5 m)</p> <p>Excavation for foundations, trenches pits etc. in ordinary soil mixed with boulders of max. dia. 600mm, including removal of vegetation, shoring, strutting, dewatering wherever necessary etc. complete. including shifting and stacking excavated material within an initial lead of 100 m, and then removal and disposing off excavated earth in MCGM / MBMC approved dumping areas (Measurements shall be based on plan dimensions of PCC. No additional payment will be made for slopes, working area, shoring, etc.)</p> <p>Rate shall be inclusive of obtaining necessary permissions from concerned statutory authorities such as Collector, MCGM debris management cell, or permissions stipulated by MBMC etc. for disposing of excavated earth for which available documents shall be provided by Tata Power</p> | 150 | M3 |
| 2 | CISE, LAYING PCC M15 | CISE, CISE, Providing all materials and laying plain cement concrete as leveling course, saddle concrete or complete encasing wherever required including formwork curing etc. Laying PCC M-15 | 15 | M3 |
| 3 | CISE, PROV & LAY CRUSHED STONE SUB BASE C | CISE, GSB: Providing & laying, spreading & compacting specified crushed stone in granular subbase course including premixing the material in mechanical mixer (pug) will carriage of mixed material laying in uniform layer of 100mm (compacted thickness each) with motor grader on prepared surface & compacting with 10 tonne vibratory roller to achieve desired density including all material, labour, machinery, lighting barricading to all lifts & lead maintenance of diversion etc. complete (metal gradation from 90mm to 75mm micron as per MCGM Road Specifications clause no. 210). | 100 | M3 |
| 4 | CISE, SCRAPING BITUMINOUS SURFACE | CISE, Scraping: Scraping Up to 60mm to 100 mm depth single pass bituminous road surface by using milling machine/JCB etc. including disposal of scraping milled materials in MCGM approved dumping yard or as directed etc. complete. Note: For further passes of 60mm or part thereof same rate will be applicable. | 100 | M2 |
| 5 | CISE, PROV & LAYING BITUMINOUS MACADAM | CISE, Providing and laying 75mm Bituminous Macadam: Bituminous Macadam: Providing and laying of 75 mm thick compacted full grout using 57mm/50mm size hand broken metal on the prepared surface to a loose thickness of 200mm by rolling with 10 ton roller including spreading, consolidation so as to obtain a compacted thickness of 75mm and spreading hot bitumen 60/70 penetration of approved brand heated to a temperature of 204 degree C (400 deg. F) by means of pressure distributor at the rate of lbs/100sft covering such area with 12.5mm size clean size stone metal at the rate of 2.1CM/100sqm and rolling the same with a 10 to 12 ton roller as directed by Tata Power engineer including providing all materials, tools equipment | 400 | M2 |

| | | | | |
|---|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|
| | | etc. | | |
| 6 | CISE,PROV & LAYIN ASPHALT CONCRETE | CISE, Providing and laying asphalt concrete (075kg/m ²): Asphalt Concrete: Providing and laying with paver asphalt concrete comprising of a thin application of fine aggregate premixed with bituminous binder including cleaning wherever required and applying tack coat (bitumen 0.75KG/m ²) Bitumen content 6.5% of mix and covered with stone dust so as to obtain the smooth finish including material tools etc.40mm thick Asphalt concrete laying by paver finisher and compaction by 10 to 12 Tone roller | 400 | M2 |
| 7 | CISE,PROV & LAYING WET MIX MACADAM | CISE, Providing and laying compacted Wet Mix Maccadam course as per mix design (MORTH) and consisting of hard quality metal 30% of size 40mm, metal 25% of size 20mm, metal 10% of size 10mm, and 35% of 6mm down and Crusher sand, by cleaning and scarifying existing uneven road surface, including Plant & Machinery for mixing in Pug Mill, laying in uniform layer of 75mm (compactedthickness each) Compaction of the prepare surface with Vibrating roller, Spreading with Paver and rolling with power roller (10 TON)and binded together with lines, grades and cross-section as shown in the attached sketch or as directed by Tata Power Site Engineer for bindage materials, grit, stone dust must be used including providing all materials, tools equipment & barricading etc. | 100 | M3 |
| 8 | P/L 12 mm thick premix seal coat | CISE, Providing &Laying with paver 12 mm thick premix seal coat comprising of a thin application of fine aggregate premix with bituminous binder. Percentage of straight bitumen shall be in the range of 6 to 8% of mix & covered with stone dust so as to obtain a smooth uniform finish including materials, tools, equipment's etc. (Rate includes laying tack coat.) | 400 | M2 |
| 9 | CISE,PROV & FIXING PAVER BLOCK 80MM THK | CISE,Providing and fixing interlocking concrete pavers of crushing strength 50N/sq mm. Concrete paver pavers shall be uniformly shaped with thickness of 80mm and in required colors. The pavers shall be placed on sand bed of 50mm thickness with proper compacting and in proper level grade and camber as directed. The side joint s shall be filled by M-20 grade PCC | 50 | M2 |

| | | | | |
|----|---------------------------------------|-----------------------------------------------------------------------------------------------------------------|-----|----|
| 10 | CISE,Removal of existing paver blocks | CISE,Removal of existing paver blocks of 60mm to 80 mm & kept in OWNER primises | 400 | M2 |
| 11 | Re-fixing of Existing Paver Block | Re-fixing of existing paver block including all labour as complete job as directed by Owners & Engineers. CISE, | 400 | M2 |

Note: Above Quantities are tentative. Tata Power reserves the right to curtailed / enhance the quantities before the placement of Purchase Order.

It may be noted that all future correspondence will be strictly done only with Interested Vendors who have done the above steps (As mentioned in section "B") in time with Authorized Person, and only through Tata Power E-Tender System.
